



# **RAYNGUARD**

**Premium Pavement Materials**

# **CrackFiller**

**Cold Pour Formula**

## **Premium Cold Pour CrackFiller**

**RaynGuard CrackFiller is a polymer enhanced blend of asphalt emulsion and select quality ingredients.**

**Suitable for cracks up to 1/2" wide in asphalt or concrete.**

**Cracks must be clean of all loose and foreign material and thoroughly dry before filling. RaynGuard Crackfiller is ready to use as received. No additional additives are required. Do not dilute. Please mix thoroughly before using. Apply by pouring, using a pour pot or suitable crack sealing applicator, fill cracks to the surface and smooth out any excess with a "V" shaped rubber squeegee.**

**Do not apply during or when rain is imminent. Application temperature should be 52°F and rising. Store in a cool, dry place. Do not allow to freeze. Coverage rate per 5 gallon bucket is approximately 315 linear feet for 1/2" x 1/2" cracks. For very deep cracks you may fill the cracks with sand or backer rod to a level 3/4" to 1" below the surface.**

**RaynGuard CrackFiller is water soluble. Tools and equipment may be cleaned with water. Once cured, a suitable solvent will be required.**

**RaynGuard Protective Materials, 8280 14th Avenue, Sacramento, CA 95826  
1-916-454-2560**