

MATERIAL SAFETY DATA SHEET

HE093 - DUROFLEX ASPHALT CRACK AND JOINT SEALANT

1. Product And Company Identification	
Supplier HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com	Manufacturer HENRY COMPANY 909 N. Sepulveda Blvd., Suite 650 El Segundo, CA 90245-2724 Company Contact: Technical Services Telephone Number: (800) 486-1278 Web Site: www.henry.com www.bakor.com
Supplier Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666	Manufacturer Emergency Contacts & Phone Number CHEMTREC: (800) 424-9300 CHEMTREC: (703) 527-3887 CANUTEC: (613) 996-6666
Issue Date: 06/16/2010 Product Name: HE093 - DUROFLEX ASPHALT CRACK AND JOINT SEALANT Product Code: HE093	

2. Composition/Information On Ingredients			
Ingredient Name	CAS Number		Percent Of Total Weight
petroleum asphalt	mixture		50 - 75
calcium carbonate	1317-65-3		25 - 45
polyether polyol	9082-00-2		1 - 10
polymer blend	NA - Mixture		5 - 15

EMERGENCY OVERVIEW	
CAUTION! Vapor may cause light-headedness, headache, nausea, loss of coordination and respiratory tract irritation. Causes skin irritation.	
Appearance/Odor: Black semi-solid, faint petroleum solvent odor	

3. Hazards Identification
Primary Routes(s) Of Entry Inhalation
Eye Hazards May cause eye irritation (burning, tearing, redness or swelling).
Skin Hazards May cause skin irritation and contact dermatitis upon prolonged contact.
Ingestion Hazards May be harmful if swallowed. May cause gastric distress, vomiting and diarrhea.
Inhalation Hazards Exposure to vapors, dusts or mists may cause respiratory tract irritation. Inhalation of vapors or mists may cause central nervous system depression, light-headedness, headache, nausea and loss of coordination.
Chronic/Carcinogenicity Effects None of the ingredients of this product comprising over 0.1% are classified as carcinogenic according to OSHA, National Toxicology Program (NTP), International Agency for Research on Cancer (IARC) or the American Conference of

HE093 - DUROFLEX ASPHALT CRACK AND JOINT SEALANT

3. Hazards Identification - Continued
<p><u>Chronic/Carcinogenicity Effects - Continued</u> Governmental Industrial Hygienists (ACGIH).</p>
4. First Aid Measures
<p><u>Eye</u> In case of contact, hold eyelids apart and immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately if irritation develops and persists.</p> <p><u>Skin</u> Remove contaminated clothing and shoes. Wash affected areas with soap and water.</p> <p><u>Ingestion</u> Get medical attention immediately. DO NOT INDUCE VOMITING. Never give anything by mouth to an unconscious victim. Call a physician or poison control center immediately.</p> <p><u>Inhalation</u> Remove the person from the contaminated area to fresh air. If breathing is difficult, give oxygen. Get medical attention immediately.</p>
5. Fire Fighting Measures
<p>Flash Point: 550F °F Flash Point Method: closed cup Lower Explosive Limit: 1.0 Upper Explosive Limit: 6.0</p> <p><u>Fire And Explosion Hazards</u> Thermal decomposition (burning) may release irritating, corrosive and/or toxic gases, vapors and fumes.</p> <p><u>Extinguishing Media</u> Chemical foam, carbon dioxide (CO2), water fog or dry chemical.</p> <p><u>Fire Fighting Instructions</u> Firefighters should wear self-contained breathing apparatus and full protective gear.</p>
6. Accidental Release Measures
<p>Contain and/or absorb spill with inert material (e.g. sand, vermiculite). Collect and dispose in accordance with applicable regulations.</p>
7. Handling And Storage
<p><u>Handling And Storage Precautions</u> Keep containers tightly closed. Store in a cool, dry, well-ventilated area. Do not handle or store near strong oxidants or strong acids. Use only with adequate ventilation.</p>
8. Exposure Controls/Personal Protection
<p><u>Engineering Controls</u> Use with adequate general and local exhaust ventilation. When used outdoors, stay well away from building air intakes or close and seal the intakes to prevent product from entering building.</p> <p><u>Eye/Face Protection</u> Safety glasses with side shields or goggles recommended.</p> <p><u>Skin Protection</u> Use with chemical-protective gloves to prevent skin contact.</p> <p><u>Respiratory Protection</u> This product is an encapsulated mixture which reduces the likelihood of exposure to hazardous particulates. Airborne exposures to hazardous dusts or mists may be generated by spraying, sanding or grinding.</p>

HE093 - DUROFLEX ASPHALT CRACK AND JOINT SEALANT

<p>8. Exposure Controls/Personal Protection - Continued</p> <p><u>Respiratory Protection - Continued</u> The level of respiratory protection needed should be based on the evaluation of chemical exposures by a health or safety professional. If required, use a NIOSH-approved air purifying respirator with organic vapor cartridge and particulate filter or supplied air respirator.</p> <p>Occupational Exposure Limits for individual ingredients (if available) are listed below.</p> <p><u>Ingredient(s) - Exposure Limits</u> petroleum asphalt ACGIH TLV-TWA 0.5 mg/m3 (inhalable fraction, as benzene-soluble aerosol) calcium carbonate OSHA PEL-TWA 15 mg/m3 (total dust) OSHA PEL-TWA 5 mg/m3 (respirable dust)</p>
<p>9. Physical And Chemical Properties</p> <p><u>Appearance</u> Black semi-solid</p> <p><u>Odor</u> Faint petroleum solvent odor</p> <p>Chemical Type: Mixture Physical State: Solid Melting Point: 220 °F Specific Gravity: 1.12 Vapor Pressure: not available Vapor Density: >1 pH Factor: not available Solubility: insoluble in water Evaporation Rate: <1</p>
<p>10. Stability And Reactivity</p> <p>Stability: Stable Hazardous Polymerization: Will not occur</p> <p><u>Incompatible Materials</u> Avoid contact with strong oxidizing agents and acids.</p> <p><u>Hazardous Decomposition Products</u> Toxic and irritating gases, vapors or fumes, carbon monoxide (CO), carbon dioxide (CO2).</p>
<p>11. Toxicological Information</p> <p><u>Miscellaneous Toxicological Information</u> Toxicological testing has not been conducted for this product overall. Available toxicological data for individual ingredients are summarized below.</p> <p><u>Ingredient(s) - Toxicological Data</u> calcium carbonate oral-rat LD50: 6450 mg/kg</p>
<p>12. Ecological Information</p> <p>No specific information available.</p>

MATERIAL SAFETY DATA SHEET

HE093 - DUROFLEX ASPHALT CRACK AND JOINT SEALANT

13. Disposal Considerations

Dispose in accordance with applicable federal, state and local government regulations.

14. Transport Information

Ground Not Restricted

IMDG Not Restricted

IATA Not Restricted

15. Regulatory Information

U.S. Regulatory Information

Asphalt may contain detectable amounts of chemicals known to the State of California to cause cancer or reproductive harm.

Ingredient(s) - State Regulations

petroleum asphalt

New Jersey - Workplace Hazard

Pennsylvania - Workplace Hazard

Massachusetts - Hazardous Substance

New York City - Hazardous Substance


calcium carbonate

Pennsylvania - Workplace Hazard

Canadian Regulatory Information

This product has been classified in accordance with the hazard criteria of the CPR and the MSDS contains all the information required by the CPR. WHMIS Classification: D2B - Toxic

NFPA



HMIS

HEALTH	1
FLAMMABILITY	1
REACTIVITY	0
PERSONAL PROTECTION	

16. Other Information

Revision/Preparer Information

This MSDS Supersedes A Previous MSDS Dated: 02/25/2010

Disclaimer

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained therein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purposes(s).