



8280 14th Avenue  
Sacramento CA 95826  
916-454-2560  
Fax: 916-452-1836  
RaynGuard.com

TECHICAL DATA SHEET  
**OIL SPOT  
SEALER**  
**READY TO USE**

**RaynGuard Oil Spot Seal** is a specially blended copolymer emulsion designed to seal grease spots and oil contaminated areas, and to improve the adhesion of seal coat.

**Suggested Use:** Use on areas contaminated by grease, oil, fuel spills, tree sap and pollen. Use to prevent grease, oil and contaminants from bleeding up through the sealcoating. Any area that is so saturated that the asphalt is soft and crumbling, should be dug out and patched.

**Features:** Seals oil spots on asphalt surfaces and gives the new seal something to bond to. Improves surface appearance.

**Preparation:** Thoroughly clean soiled areas with a scraper, wire brush, torch, power washer, etc.

**Directions for Use:** Ready to use straight from the container

**Precautions:**

- Place a thin coat of material onto the surface and brush, spray, or roll onto the affected areas, being sure to overlap 2 inches beyond the stain.
- Allow 1-3 hours for drying, after which the area should be seal coated immediately.
- Do not apply to wet surfaces or on days when rain is forecast.
- Ideal conditions are 50°F and rising with sunny weather.
- **Do not use two coats!** One coat only.
- Do not store in temperatures above 100 degrees.
- Keep from freezing.
- Keep out of reach of children.

**Clean Up:** Clean tools with water before material dries.

**Packaging:** Available in 5 gallon pails

**Color:** Grey/Black  
**Viscosity:** 50 KU  
**Solids:** 25-30% )  
**pH:** 4.5  
**Density:** 8.5-9