



TECHNICAL DATA SHEET

RAYNGUARD QUICK DRY

RaynGuard Quick Dry is a complex copolymer emulsion designed to modify asphalt based sealers. This product is designed to enhance the sealer's dry/cure time while improving the overall toughness and adhesion qualities.

Available in one or five gallon pails.

ADVANTAGES

- Promotes quicker water release and enhances drying and curing times.
- Improves the heat and moisture resistance of the asphalt sealer.
- Adds to the overall toughness of the finished product. Improvement in dry film strength.

APPLICATION

While mixing tank agitator is turning, add 1% RaynGuard Quick Dry by volume to asphalt sealer. Dilute the mixture with water only if necessary. **Once thoroughly mixed you must immediately apply the finished product to the pavement.** Quick Dry, once mixed, is most active during the first 60-90 minutes, only mix what you will use in this time frame.

TRANSPORTATION, STORAGE & HANDLING

- DOT: not regulated.
- Keep/store out of direct sunlight.
- Do not allow to freeze prior to application.
- Keep containers tightly sealed when not in use.
- Avoid prolonged skin contact.
- Do not take internally.
- Store, handle and dispose per SDS requirements.

PHYSICAL PROPERTIES

Color	White
Viscosity	2200-2500 cps @ 77° F
Solids	Approximately 56%
pH	8.0 – 9.5
Density	9 lbs/gal

MANUFACTURED & PACKAGED BY

RaynGuard Protective Materials, Inc.
8280 14th Avenue
Sacramento, CA 95826
+1 (916) 454-2560
www.raynguard.com